



# SHEET METAL CONNECTORS, INC.

www.smduct.com

MINNEAPOLIS, MN  
 5850 Main Street N.E.  
 Minneapolis, Minnesota 55432  
 LOCALLY CALL: 763-572-0000  
 TOLL FREE: 1-800-328-1966  
 FAX: 763-572-1100

ROCKFORD, IL  
 5601 Sandy Hollow Road  
 Rockford, Illinois 61109  
 LOCALLY CALL: 815-874-4600  
 TOLL FREE: 1-866-504-4600  
 FAX: 815-874-9979





## 2" Standoff Collars with Damper

Sheet Metal Connectors' stand-off collars are fabricated from galvanized steel. These collars have a crimp and stop bead on one end. The volume damper is made out of 20 ga. galvanized steel with stiffening beads and a continuous 3/8" aluminum square shaft for strength and rigidity. Nylon end bearings are added to each end to reduce air leakage. All standoff collars have a 3/8" dial regulator elevated 2" for insulation.

### Sleeve with 2" Standoff

Order as follows: A = Diameter




A	Length
6"	6 3/16"
7"	6 3/16"
8"	6 3/16"
9"	6 3/16"
10"	6 3/16"
12"	8"
14"	12"
16"	12"
18"	13"
20"	15"

### E-Z Tap Collars with 2" Standoff

Order as follows: A = Diameter

All Fittings are 1.75" from Bead to End of Fitting.




A	Overall Length
5"	5"
6"	5"
7"	5"
8"	5"
9"	5"
10"	5"
12"	7"
14"	7"
16"	7"
18"	10"
20"	10"
22"	10"
24"	10"

### Conical E-Z Tap with 2" Standoff

Order as follows: A = Diameter


\*Complete Seal Standard



A	Overall Length
6"	9 1/4"
8"	9 1/4"
10"	9 1/4"
12"	9 1/4"

### Super Heto with 2" Standoff

Order as follows: A = Diameter



A	Overall Length
6"	8"
8"	9"
10"	9"
12"	9"
14"	9"

All Fittings are 1.75" from Bead to End of Fitting.

