SHEET METAL CONNECTORS, INC.

www.smcduct.com

MINNEAPOLIS, MN
5850 Main Street N.E.
Minneapolis, Minnesota 55432
LOCALLY CALL: 763-572-0000
TOLL FREE: 1-800-328-1966
FAX: 763-572-1100

ROCKFORD, IL
5601 Sandy Hollow Road
Rockford, Illinois 61109
LOCALLY CALL: 815-874-4600
TOLL FREE: 1-866-504-4600
FAX: 815-874-9979

2” Standoff Collars with Damper

Sheet Metal Connectors’ stand-off collars are fabricated from galvanized steel. These collars have a crimp and stop bead on one end. The volume damper is made out of 20 ga. galvanized steel with stiffening beads and a continuous 3/8” aluminum square shaft for strength and rigidity. Nylon end bearings are added to each end to reduce air leakage. All standoff collars have a 3/8” dial regulator eleveated 2” for insulation.

Sleeve with 2” Standoff

Order as follows: A = Diameter





A	Length
6”	6 3/16”
7”	6 3/16”
8”	6 3/16”
9”	6 3/16”
10”	6 3/16”
12”	8”
14”	12”
16”	12”
18”	13”
20”	15”

E-Z Tap Collars with 2” Standoff

Order as follows: A = Diameter

All Fittings are 1.75” from Bead to End of Fitting.



A	Overall Length
5”	5”
6”	5”
7”	5”
8”	5”
9”	5”
10”	5”
12”	7”
14”	7”
16”	7”
18”	10”
20”	10”
22”	10”
24”	10”

Conical E-Z Tap with 2” Standoff

Order as follows: A = Diameter

*Complete Seal Standard



A	Overall Length
6”	9 1/4”
8”	9 1/4”
10”	9 1/4”
12”	9 1/4”

Super Heto with 2” Standoff

Order as follows: A = Diameter



A	Overall Length
6”	8”
8”	9”
10”	9”
12”	9”
14”	9”

All Fittings are 1.75” from Bead to End of Fitting.

YELLOW LABEL