





Series SDD

Double Deflection Spiral Duct Diffuser



- Double Deflection
- Sunken Screw Holes
- Adjustable Blades
- Gaskets on Margin
- Optional Scoop Available (pictured)
- Galvanized Finish
- Made in the U.S.A.



Face Velocity		300	400	500	600	700	800	1000	1200
Total Pressure		0.016	0.029	0.046	0.066	0.090	0.117	0.183	0.263
10 x 3 Ak .14	CFM	42	56	70	84	98	112	140	168
	Horizontal Throw	7-3	8-4	9-5	10-6	11-7	12-8	13-9	14-10
	Noise Criteria	--	--	--	--	--	23	29	35
12 x 3 Ak .18	CFM	54	72	90	108	126	144	180	216
	Horizontal Throw	8-5	9-6	10-7	11-8	12-8	13-9	14-10	16-11
	Noise Criteria	--	--	--	--	20	24	31	36
10 x 4 14 x 3 Ak .21	CFM	63	84	105	126	147	168	210	252
	Horizontal Throw	8-5	10-7	11-8	12-8	13-9	14-10	16-11	17-12
	Noise Criteria	--	--	--	--	21	25	31	37

Performance Data, Series SDD (continued)

Face Velocity		300	400	500	600	700	800	1000	1200
Total Pressure		0.016	0.029	0.046	0.066	0.090	0.117	0.183	0.263
16 x 3 12 x 4 Ak .25	CFM	75	100	125	150	175	200	250	300
	Horizontal Throw	9-5	11-7	12-8	13-9	14-10	15-11	17-12	19-13
	Noise Criteria	--	--	--	--	21	25	32	37
24 x 3 12 x 6 Ak .39	CFM	117	156	195	234	273	312	390	468
	Horizontal Throw	12-7	13-9	15-10	17-11	18-12	19-13	21-15	24-16
	Noise Criteria	--	--	--	--	23	27	34	39
24 x 4 16 x 6 Ak .52	CFM	156	208	260	312	364	416	520	624
	Horizontal Throw	13-8	16-11	18-12	19-13	21-14	22-15	25-17	27-19
	Noise Criteria	--	--	--	20	24	28	35	40
14 x 8 18 x 6 Ak .63	CFM	189	252	315	378	441	504	630	756
	Horizontal Throw	15-8	17-12	19-13	21-14	23-16	24-17	27-19	30-20
	Noise Criteria	--	--	--	20	25	29	36	41
20 x 6 Ak .66	CFM	198	264	330	396	462	528	660	792
	Horizontal Throw	15-9	18-12	20-13	22-15	24-16	25-17	28-19	31-21
	Noise Criteria	--	--	--	21	25	29	36	41
16 x 8 Ak .71	CFM	213	284	355	426	497	568	710	852
	Horizontal Throw	16-9	18-13	20-14	23-15	24-17	26-18	30-20	35-22
	Noise Criteria	--	--	--	21	26	30	36	42
24 x 6 18 x 8 Ak .88	CFM	264	352	440	528	616	704	880	1056
	Horizontal Throw	18-10	20-14	23-16	25-17	27-18	29-20	32-22	36-24
	Noise Criteria	--	--	--	22	26	30	37	43
20 x 8 16 x 10 Ak .98	CFM	294	392	490	588	686	784	980	1176
	Horizontal Throw	19-10	21-15	24-17	26-18	28-19	30-21	34-23	38-25
	Noise Criteria	--	--	--	23	27	31	38	44
18 x 10 Ak 1.11	CFM	333	444	555	666	777	888	1110	1332
	Horizontal Throw	20-11	23-16	25-18	28-19	30-21	32-22	36-25	40-27
	Noise Criteria	--	--	--	23	27	31	38	44
36 x 6 18 x 12 Ak 1.35	CFM	405	540	675	810	945	1080	1350	1620
	Horizontal Throw	22-12	25-17	28-19	31-21	34-23	36-24	40-27	44-30
	Noise Criteria	--	--	--	24	28	32	39	44
24 x 10 20 x 12 Ak 1.49	CFM	447	596	745	894	1043	1192	1490	1788
	Horizontal Throw	23-13	26-18	30-20	32-22	35-24	37-26	42-29	46-31
	Noise Criteria	--	--	--	24	29	33	39	45
24 x 12 Ak 1.82	CFM	546	728	910	1092	1274	1456	1820	2184
	Horizontal Throw	25-14	30-20	33-22	36-25	39-27	42-28	47-32	51-35
	Noise Criteria	--	--	--	25	30	34	40	46
36 x 10 30 x 12 Ak 2.29	CFM	687	916	1145	1374	1603	1832	2290	2748
	Horizontal Throw	29-16	33-22	37-25	41-28	44-30	47-32	53-36	61-42
	Noise Criteria	--	--	20	26	30	34	41	47
36 x 12 Ak 2.75	CFM	825	1100	1375	1650	1925	2200	2750	3300
	Horizontal Throw	31-18	36--25	41-28	44-30	48-33	51-35	57-39	63-43
	Noise Criteria	--	--	21	27	31	35	42	47